Int'l Appl. No.

PCT/JP2003/014570

Int'l Filing Date

November 17, 2003

AMENDMENTS TO THE CLAIMS

Please amend the Claims as follows. Insertions are shown <u>underlined</u> while deletions are struck through. Please add Claims 11-

1 (original): A curing resin composition containing

a siloxane oligomer (A) having an average molecular weight of 500 to 10000 in terms of ethylene glycol and

a fluorine compound (B) having a fluoroalkyl structure and a polysiloxane structure and having a number average molecular weight of 5000 or more in terms of polystyrene.

- 2 (original): The curing resin composition according to claim 1, wherein a fluorine atom content in the curing resin composition is 20 wt % or more.
- 3 (currently amended): The curing resin composition according to claim 1-or 2, further containing a crosslinking compound.
- 4 (currently amended): The curing resin composition according to any of claims 1 to 3, further containing an acid generating agent.
- 5 (currently amended): A cured film obtained by curing a curing resin composition according to any of claims 1-to 4.
- 6 (original): The cured film according to claim 5, wherein a ratio (Si/F) of a peak intensity of a silicon atom (Si) to a peak intensity of a fluorine atom (F) on a surface of the cured film as measured with an X-ray photoelectron spectroscopic method is in the range of from 0.4 to 2.

7 (currently amended): An antireflection film comprising a hard coat layer formed on one surface of a transparent substrate directly or with another layer interposed there between and an antireflection layer laminated on a surface of the hard coat layer, wherein the antireflection layer is constituted of a cured film according to claim 5-or-6.

- 8 (original): The antireflection film according to claim 7, wherein a surface of the hard coat layer has irregularity of protrusions and depressions combined and an antiglareness.
- 9 (currently amended): An optical element on one surface or both surfaces of which an antireflection film or antireflection films according to claim 7-or-8 are provided.
- 10 (currently amended): An image display to which an antireflection film according to claim 7-or 8 or the optical element according to claim 9 is mounted.
- 11 (new): The curing resin composition according to claim 2, further containing a crosslinking compound.

Int'l Appl. No. : PCT/JP2003/014570 Int'l Filing Date : November 17, 2003

12 (new): The curing resin composition according to claim2, further containing an acid generating agent.

13 (new): The curing resin composition according to claim 3, further containing an acid generating agent.

14 (new): The curing resin composition according to claim 11, further containing an acid generating agent.

15 (new): A curable resin composition comprising:

- (A) a siloxane oligomer having an average molecular weight of 500 to 10000 in terms of ethylene glycol; and
- (B) a fluorine compound having a fluoroalkyl structure and a polysiloxane structure and having a number average molecular weight of 5000 or more in terms of polystyrene, wherein a ratio of A/(A+B) by solid weight is 0.05-0.9,

said composition being curable by heat or active light irradiation by reacting the siloxane oligomer and the polysiloxane structure in the fluorine compound.

16 (new): The curable resin composition according to claim 15, wherein the fluorine compound contains a hydroxyl group and/or an epoxy group which are reactive with the siloxane oligomer or the polysiloxane structure in the fluorine compound.

17 (new): The curable resin composition according to claim 15, further comprising a crosslinking agent in an amount of 70 parts or less by weight with respect to the fluorine compound.

18 (new): A cured film using the curable resin composition of claim 15, having a cured structure of: (A) the siloxane oligomerglycol and (B) the fluorine compound, said siloxane oligomer and said polysiloxane structure in the fluorine compound being reacted.

19 (new): The cured film according to claim 18, which has an additional cured structure wherein the fluorine compound contains a hydroxyl group and/or an epoxy group which have reacted the siloxane oligomer or the polysiloxane structure in the fluorine compound.